





Product Service

# CERTIFICATE

No. Z2 099333 0045 Rev. 06

## Model(s):

LR6-72HV-xxxM, (xxx=335-360 in step of 5)  
 LR6-60HV-xxxM, (xxx=280-300 in step of 5)  
 LR6-72PH-xxxM, (xxx=340-380 in step of 5)  
 LR6-60PH-xxxM, (xxx=285-315 in step of 5)  
 LR6-72HPH-xxxM, (xxx=365-395 in step of 5)  
 LR6-72HIH-xxxM, (xxx=365-395 in step of 5)  
 LR6-60HPH-xxxM, (xxx=300-325, in step of 5)  
 LR6-60HIH-xxxM, (xxx=300-325 in step of 5)  
 LR6-72OPH-xxxM, (xxx=385-415 in step of 5)  
 LR6-60OPH-xxxM, (xxx=335-365 in step of 5)  
 LR6-72HPH-xxxMC, (xxx=375-390 in step of 5)  
 LR6-60HPH-xxxMC, (xxx=305-325 in step of 5)  
 LR6-60ZPH-xxxM, (xxx=330-355 in step of 5)  
 LR4-72HPH-xxxM, (xxx=420-445 in step of 5)  
 LR4-72HIH-xxxM, (xxx=420-440 in step of 5)  
 LR4-60HPH-xxxM, (xxx=350-370 in step of 5)  
 LR4-60HIH-xxxM, (xxx=350-370 in step of 5)  
 LR4-72ZPH-xxxM, (xxx=420-435 in step of 5)  
 LR4-60ZPH-xxxM, (xxx=350-365 in step of 5)  
 xxx is standing for rated output power at STC

## Parameters:

Fire Safety Class:	Class C according to UL790.
Safety Class:	Class II
Max. System Voltage:	1500V DC
Test Laboratory:	Yangzhou Opto-Electrical Products Testing Institute. No.10 West Kaifa Road, Yangzhou, 225009 Jiangsu, P.R.China.
Construction:	Framed, with Junction box, cable and connector.

## Tested according to:

IEC 61215-1:2016  
 IEC 61215-1-1:2016  
 IEC 61215-2:2016  
 IEC 61730-1:2016  
 IEC 61730-2:2016  
 EN 61215-1:2016  
 EN 61215-1-1:2016  
 EN 61215-2:2017  
 EN IEC 61730-1:2018  
 EN IEC 61730-1:2018/AC:2018-06  
 EN IEC 61730-2:2018  
 EN IEC 61730-2:2018/AC:2018-06

## Production Facility(ies):

099605, 099626, 099606, 090968, 001192, 002875, 096558,  
 102892, 097323, 103410, 103841

TÜV SÜD TÜV SÜD TÜV SÜD TÜV SÜD TÜV SÜD TÜV SÜD TÜV SÜD TÜV SÜD TÜV SÜD TÜV SÜD TÜV SÜD TÜV SÜD TÜV SÜD TÜV SÜD  
 ZERTIFIKAT ◆ CERTIFICATE ◆ 認證證書 ◆ CERTIFICADO ◆ CERTIFICAT

A4 / 07.17